

ANALOGUE 1-, 2- AND 3-AXIS INDUSTRIAL JOYSTICK MJ-3K CP



The MJ-3K joystick series offers compact and robust industrial joysticks that can be supplied with conductive-plastic potentiometer sensor elements in analogue versions as well as with galvanically isolated direction contacts. The joysticks are available with 1, 2 or 3 axes for applications such as the safety radio remote control of machinery and systems or for mobile hydraulic applications.

FEATURES

- Long service life
- Robust design
- Compact
- Conductive plastic technology

APPLICATIONS

- Aerial work platforms
- Wireless remote controls
- Forklift trucks
- Mobile hydraulics
- Steering of boats

OPTIONS

- Grip length 55
- Grip length 65



ELECTRICAL SPECIFICATIONS

Resistance value	5 kΩ *
Resistance tolerance	± 20%
Deflection angle, el.	> ± 26° *
Independent linearity	± 2%
Zero position switch per axis	< ± 3° open
Load capacity/axis	0,2 W at 40°C
Operating voltage (VCC)	Max. 30 VDC
Contact current	< 10 μA
Max. contact current	1 mA in case of malfunction
Insulation resistance	1 GΩ at 500 VDC
Dielectric strength	2000 V

MECHANICAL SPECIFICATIONS

Service life	5 million cycles
--------------	------------------

Specifications are subject to change without notice.
* Other values on request.

Deflection angle, mech.	± 26°
Operating force	5 N typically
Gate shape	Square, soft cross guide
Wiper zero position	± 1°
Impact strength	100 N
User control	Handle with Gaiter

AMBIENT CONDITIONS

Storage temperature	-40°C ... +85°C
Operating temperature	-25°C ... +70°C
Protection class	IP 65



MATERIALS

Base	Aluminium
Bearing	Stainless steel/plastic
Electrical connection	12-pin Hirose plug, 6-pin Dubox plug
Mounting	Screws M3

MJ-3K CP (CONDUCTIVE PLASTIC) ANALOGUE

Type	MJ-3K 55 CP X:0 Y:5K MC 1-0-1 Hirose 12-pin	Type	MJ-3K 65 CP XY:2.5k 1-0-1 Dubox 6-pin
Item number	E060200038	Item number	E060200466 [2-axis]
Type	MJ-3K 55 CP XY:5K MC 1-0-1 Hirose 12-pin	Type	MJ-3K 65 CP XY:5K MC 1-0-1 Hirose 12-pin
Item number	E060200037	Item number	E060200444 [2-axis]
Type	MJ-3K 55 CP X:0 Y:2.5K 1-0-1 Dubox 6-pin	Type	Hirose 12-pin (ws) LiYv 0.14mm² 500mm
Item number	E060200487 [1-axis]	Item number	Z301000512
Type	MJ-3K 55 CP XY:2.5k 1-0-1 Dubox 6-pin	Connection cable	Dubox 6-pin LiYv 0.14mm² 500mm
Item number	E060200465 [2-axis]	Item number	Z301000500



DRAWINGS FOR MJ-3K CP 65



Assembly into Housing from Inside / Screw Head outside of housing
If thickness of mounting panel is 3mm:
Use Screw M3x10mm / Center Hole D=49.0

Male Connector HIROSE
No.: 543-0041-7-01
pitch: 2.0/12-pole (black)

CONNECTOR PIN ASSIGNMENT / DIAGRAM



Connect. Resistance 5 kOhm $\pm 20\%$
Analogue band 10% - 90% $U_{total} \pm 3\%$
Medium Voltage 50% $U_{total} \pm 2.5\%$
Linearity $\pm 2\%$
Contact Resistance Switch $< 1 \text{ kOhm}$
Life CP/PCB $> 5 \text{ Mio Cycles}$