

PNOZ 2VQ 24VDC 3n/o 1n/c 2n/o t

774013



Safety relay (standalone) Inputs: 1-/2-channel wiring with/without detection of shorts across contacts. Outputs: 3 N/O, 1 N/C, 2 N/O delayed UB 24 V DC, width: 112.5 mm, integral screw terminals Monitoring E-STOP, safety gates with two freely selectable delay-on de-energisation contacts, 12 stages from 0 - 20/0 - 3 s.

技术细节

批准:	CE;cULus 认证;TÜV;CCC
应用选项:	安全门监控;瞬时紧急停止监控;限位开关;紧急停止延时监控
操作模式:	单通道;自动复位;双通道;手动复位;触点间短路检测;不检测触点间短路
产品标准:	EN 60947-5-1
标准:	EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1
供电电压 (V):	24,0
电源类型:	DC
终端型:	固定式
终端类型:	螺丝端子
瞬时安全触点数量:	3
延时安全触点数量:	2
安全触点延时类型:	延时断电
辅助触点数量:	1
停止类别:	0/1
在DC13处的最大电流I (6个循环/最小):	7.0 A
在AC1处的最大电流5:	5.0 A
宽度尺寸:	112.5 mm
高度尺寸:	87.0 mm
深度尺寸:	121.0 mm
总重:	615 g



THE SPIRIT OF SAFETY

净重:	600 g
以摄氏度一表示的环境温度:	-10 - 55 °C